Nuaire LabGard ES 813 Class I Biological Safety Cabinet

The LabGard ES 813 Class I Biological Safety Cabinet can be used as a balance enclosure or ductless fume hood for personnel protection for the safe handling of low risk powders, liquids, and animal necropsy.

Rating: Not Rated Yet

Ask a question about this product

Manufacturer Nuaire

Description



Energy Efficiency Consumes low energy with quality functions



Ergonomic Design Contributes to a friendly working environment



Dynamic Air Block Assures strong inflow air velocity and maximum personnel protection

- Features
- Specifications
- Optional Features

Features

Energy Saver Motor

An ultra high efficiency motor saves on your energy bills while increasing filter life lowering your total cost of ownership.

FlowGard Control System

A pressure monitor constantly inspects plenum pressure alerting to any imbalances in airflow.

Dynamic Air Barrier

Strong inflow air velocity at 80 fpm (.40 m/s) creates personnel protection

Bag-In Bag-Out Filter System Simplified way for technicans to remove the exhaust HEPA filter without exposing themselves to potential contaminates after decontamination procedures.

Self Exhausting Two Service Ports Hinged Viewing Polycarbonate Window Clear Polycarbonate Side Panels White Polycarbonate Back Panel Coved Stain Resistant Black Epoxy Black Work surface 99.99% @ 0.3 Micron Exhaust HEPA Filter T5 Fluorescent Cool White Lighting

Specifications

Model Nominal Size Style of Cabinet	NU-813-300 3 ft [0.9 m] Bench top/console with optional base stand	NU-813-400 4 ft [1.2 m] Bench top/console with optional base stand	
Sash Height	8" [203 mm]	8" [203 mm]	8" [203 mm]
Exterior	36 x 29 x 51 1/2	48 x 29 x 51 1/2	77 x 29 x 51 1/2
Dimensions	[914 x 737 x	[1219 x 737 x	[1829 x 737 x
$(W \times D \times H)$	1308]	1308]	1308]
in. [mm]			
Interior		46 3/8 x 24 x 28	70 3/8 x 24 x 28
Dimensions	[873 x 610 x 711]	[1178 x 610 x 711]	•
(W x D x H)			711]
in. [mm]			
Weight	300 lbs. / 136 kg.	400 lbs. / 181 kg.	500 lbs. / 227 kg.
Sound			
Pressure			
Level	0 450 (500	0 450/500	0 450 (500
Light Intensity foot-	0 - 150 (538 -	0 - 150 (538 - 1600)	0 - 150 (538 - 1600)
candles	- 1000)	1600)	1600)
(LUX)			
(LUA)			

Warranty

3 Year Parts and Labor (US & CA)

4 Year Parts (Intl)

Accolades

UL, UL-C, CE, Energy Saver, Personnel Protection, Environmental Protection, Routinely tested to ANSI\ASHRAE 110, Surrogate Powder, and Biological

Please note specifications are subject to change. Please contact NuAire to verify before purchase

Optional Features

Optional Features

Purafil® Filter (in lieu of HEPA) Charcoal Filter (in lieu of HEPA) Base Support Stands Service Valves for Gas, Air, Vac Seismic Brackets

Reviews

There are yet no reviews for this product.