



K Series



Reliable and Efficient Storage

K Series

The K Series cryogenic systems offer reliable liquid nitrogen storage with controllable temperatures between -100°C to -196°C . Combined with the safety of the automatic alarms and the easy access to stored product, the unique Temperature Gradient Suppression System greatly improves vapor phase temperature storage and recovery.

K Series

Features

- Vapor or liquid storage
- Intuitive Touch Controls
- Kryos (battery option) or AutoTend
- Stainless Steel vacuum vessel
- Modular design
- Durable powder coated cabinet
- Caster mounted
- Superior vacuum performance



(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.

(2) Working Time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.

(3) Maximum required clearance (with lid open) for the 10K is 69.0 (1753 mm); 24K is 76.0 in. (1930mm). Depth with lid open for 10K is 34.0 (864 mm); 24K is 48.5 (1232 mm).

(4) Maximum depth 55.0 in (1397mm). Maximum height 90.0 in. (2286 mm) with lid open.

(5) Temperature Gradient Suppression System reduces internal diameter by approx. 1/4 in. (6.4 mm).

(6) 2.0 ml vial size: 12.5 mm O.D. internal thread (7) 6 racks, 9 levels, 2" shelf height.

(8) The 10K/24K/38K containers utilize both the 5 in. x 5 in. (127 mm x 127 mm) 100/81 cell box and the 3 in. x 3 in. (76 mm x 76 mm) 25 cell box.

(9) 3K is not available with controllers.

MODEL		3K ⁽⁹⁾	10K	24K	38K
Static Holding Days ⁽¹⁾		19	33	52	74
Working Time days ⁽²⁾		12	N/A	N/A	N/A
Evaporation Rate ⁽¹⁾ liters/days		2.5	5.0	7.0	8.0
Liquid Nitrogen Capacity - liters		48	165	365	590
Weight Empty	lbs. kg.	42.0 19.1	245 111	405 184	565 256
Weight Full ⁽³⁾	lbs. kg.	125 56.7	537 243	1046 474	1616 733
Neck Diameter	in. mm.	14.0 356	21.0 533	31.0 787	39.0 991
Overall Height	in. mm.	29.7 754	44.0 111.8	44.0 111.8	49.0 1245
Overall Dimensions	in. mm.	15.4 391	23.1x30.5 ⁽³⁾ 587x775	34.0x38.5 ⁽³⁾ 864x965	42.0 ⁽⁴⁾ 1067
Usable Height - Internal	in. mm.	19.2 488	29.0 737	29.0 737	29.0 737
Internal Diameter	in. mm.	14.0 356	21.0 ⁽⁵⁾ 533	31.0 ⁽⁵⁾ 787	39.0 ⁽⁵⁾ 991
Capacity		3K ⁽⁹⁾	10K	24K	38K
2 ml Plastic Vials ⁽⁶⁾		3024	10400	24050	38350
Number of 100/81 Cell Racks		N/A	7	17	28
Number of 25 Cell Racks		N/A	4	6	6
Number of Shelves		N/A	13	13	13
Box Size					
Shape		Triangle	Square		Square
in.		6.75x6.87 ⁽⁷⁾	5x5 ⁽⁸⁾		3x3 ⁽⁸⁾
mm.		171x175	127x127		76x76
Vials per box		56	100		25
Blood Bag Capacity					
Fenwal #4R5461 - 9953	N/A	235	535	870	
Fenwal #4R5462 - 9955	N/A	185	475	680	
Fenwal #4R5451 - 9951	N/A	343	805	1407	
Stericon #RCM91D	N/A	235	360	560	
Chartmed #7005-2	N/A	105	216	536	
Gambro #DF700	N/A	88	200	320	
Gambro #DF200	N/A	192	496	496	
0.50cc straws, 10 per goblet, 2-13mm goblets per can, Two tier turn-table inventory control system	N/A	44000	59400	114000	
Roller Base	R018-8C00	N/A	N/A	N/A	
Cryo-Sentry Level Alarm	N/A	R034-8C15	R034-8C15	R037-8C15	



Taylor-Wharton
Since 1742

cryoscience@taylorwharton.com
www.taylorwharton.com

The Americas

Phone: +1 800-898-2657
Phone: +1 251-443-8680

Europe

Germany
Phone: +49 (0) 4841 9850

Slovakia

Phone: +421 (0) 55 72 77 124

Australia and Asia

Australia
Phone: +61 (0) 2 6040-2533

China

Phone: +86(0) 316-3219770

Malaysia

Phone: +60 (0)3—51913003