



LABS Series



The Benchmark in Biobanking

State-of-the art engineering design featuring:

High efficiency - very low LN₂ consumption

- LN₂ storage in either liquid or vapor phase
- Near LN₂ temperatures maintained at top of inventory storage system for overall sample viability

Single pivot point aluminum turntable design - smooth rotation and ergonomic use

- Eliminates any mechanical component maintenance
- Full height, segmented and labeled turntable provides easy inventory storage access and management

Hinged lid and stainless steel table top - easy operation with a convenient working surface

- The lid includes locking capabilities and activates an automatic defog for quick viewing of inventory storage
- The table top provides a clear working surface and provides protection to electrical and plumbing components

Enhanced and intuitive controller technology:

- Discrete thermistor level measurement and thermocouple temperature resolution 0.1° C
- Capabilities for data collection, event scheduling and enhanced security settings

LABS Series

MODELS		20K	38K	40K	80K	94K
External Operating Height (Top of Step to Lid opening)	in. mm.	42 1067	44 1118	42 1067	42 1067	40 1016
Step Height (1)	in. mm.	11 279	11.5 292	11/* 279	11/17 279	11/22 279/559
Height (Floor to Opening)	in. mm.	53 1346	56 1422	53 1346	53 1346	62 1575
Usable Height, Internal	in. mm.	30 762	30 762	30 762	30 762	35.3 897
Outside Diameter	in. mm.	34 864	42 1067	45 1143	59.5 1511	59.5 1511
Internal Working Diameter	in. mm.	29.5 750	37.8 959	40.5 1029	55 1397	55 1397
Neck Opening	in. mm.	13 330	18 457	18 457	24.5 622	24.5 622
Capacity						
Total LN ₂ Capacity (Liquid Storage)	L.	407	626	606	1350	1630
Total LN ₂ Capacity (Vapor Storage)	L.	46	72	76	150	300
Weight, Empty	lb. kg.	650 295	930 422	920 417	1550 703	1700 771
Maximum Gross Weight (3)	lb. kg.	1375 624	2050 930	2000 907	3956 1794	4600 2086
Inventory Control System Specifications						
No. 100/81 Cell Racks		14	26	30	58	60
No. Shelves/Rack		13	13	13	13	15
No. 25 Cell Racks		4	12	8	12	12
No. Shelves/Rack		13	13	13	13	15
Vial Capacity, 2 ml (4)		19500	37700	41600	79300	94500
Bag 25 ml (7 Level Rack)(5)		1624	2688	3108	5999	6856
Bag 50 ml (7 Level Rack)(5)		924	1582	1876	3381	3864
Bag 250 ml (5 Level Rack) (6)		500	900	990	1920	2304
Bag 500 ml (5 Level Rack) (6)		420	690	830	1610	1932

(1) LABS 94K features independent dual stainless steel folding steps. The dual steps are optional on the LABS 40K and 80K.
 (2) Universal transformer reduces power to 12 VDC. Power outlet/plug configuration for country of end use to be indicated at time of order. (3) Includes the empty weight and total LN₂ capacity weight. (4) 2 ml vial size/12.5 mm O.D. internal thread. 6-2 half-rack capacity of 94,200 for LABS 94. (5) Model LABS 94K, 8 Level Rack. (6) Model LABS 94K, 6 Level Rack. (7) Features standard on all units with CS Control System.

Integral folding step with slip-resistant surface



All units include a mechanical step lock for securing the step when stowed(7)



Flexible Fill Hose with 1.27 cm I.D. includes dual swivel connectors and a 3/8" male NPT adaptor⁷



Taylor-Wharton
Since 1742

cryoscience@taylorwharton.com
www.taylorwharton.com

The Americas

Phone: +1 800-898-2657
Phone: +1 251-443-8680

Europe

Germany
Phone: +49 (0) 4841 9850

Slovakia

Phone: +421 (0) 55 72 77 124

Australia and Asia

Australia
Phone: +61 (0) 2 6040-2533

China

Phone: +86(0) 316-3219770

Malaysia

Phone: +60 (0)3—51913003