



## Laboratory Systems Series

### LS Series

The Taylor-Wharton Laboratory Systems (LS) are uniquely designed for large vial capacity in convenient box-type storage racks. They provide maximum holding times. This means lower per vial operating costs and fewer refills. The new LS6000 with the Auto-Tend Controller with temperature read-out provides automatic filling and alarm features.

# LS Series

MODEL		LS750	LS3000	LS4800	LS6000	LS6000AT
Static Holding Days (1)		130	106	153	194	194
Working Time days (2)		80	66	96	120	120
Evaporation Rate (1) liters/days		0.27	0.76	0.85	0.84	0.84
Liquid Nitrogen Capacity - liters		35	81	130	165	165
Weight Empty	lbs. kg.	39 17.7	70 31.8	90 40.9	121 55.0	121 55.0
Weight Full (3)	lbs. kg.	101.3 46.0	214.2 97.4	312.4 146.1	410.0 186.4	410.0 186.4
Neck Diameter	in. mm.	4.7 119	8.5 216	8.5 216	8.5 216	8.5 216
Overall Height	in. mm.	26.8 681	28.8 731	35.1 892	39.0 991	39.0 991
Overall Diameter	in. mm.	18.8 478	26.9 683	26.9 683	26.9 683	26.9 683
Number of Racks		6	6	6	6	6
Number of Shelves/Rack		5	5	8	10	10
2 ml Vial Capacity (4)		750	3000	4800	6000	6000
Box Size - Shape		Square	Square	Square	Square	Square
Size in.		3.0 x 3.0	5.0 x 5.0	5.0 x 5.0	5.0 x 5.0	5.0 x 5.0
Size mm.		76x76	127x127	127x127	127x127	127x127
Vials per box (5)		25	100	100	100	100
Roller Base		R033-8C00	R05K-8C00	R05K-8C00	R05K-8C00	R05K-8C00
Cryo-Sentry Level Alarm		R036-8C30	RS30-8C40	R05K-8C26	RS60-8C40	N/A
Auto-Tend Controller Kit		N/A	N/A	N/A	RS60-8C86 (6)	N/A

(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.

(2) Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.

(3) Without canisters or racks.

(4) 2.0 ml vial size: 12.5 mm O.D. internal thread.

(5) 81 cell boxes available.

(6) Please contact Taylor-Wharton Customer Service for details.

## Features

- LS 6000 available with Auto-Tend Controller with temperature read-out. *(Please contact Taylor-Wharton Customer Service for details)*
- LS 6000-AT, vapor phase, -190°C top of rack
- New Rugged Construction – ribbed high strength aluminum body, magniformed necktube design, and more durable paint system
- Convenient Storage Systems – rack index location ring and internal location spider, computer compatible box storage is ideal for simple inventory management
- Superior vacuum performance with super insulation provides maximum holding times
- Security – Accessory low-level alarm is available with remote monitor capability
- Lockable lids
- Mobility – Roller bases are available



**Taylor-Wharton**  
Since 1742

cryoscience@taylorwharton.com  
www.taylorwharton.com

### The Americas

Phone: +1 800-898-2657

Phone: +1 251-443-8680

### Europe

Germany

Phone: +49 (0) 4841 9850

Slovakia

Phone: +421 (0) 55 72 77 124

### Australia and Asia

Australia

Phone: +61 (0) 2 6040-2533

China

Phone: +86(0) 316-3219770

Malaysia

Phone: +60 (0)3—51913003